MECHANICAL PLAN NOTES:

- (1) EXISTING FAN COIL UNIT RELOCATED TO NOT BE IN CONFLICT WITH NEW DISHWASHER OR LIGHTS. CONTRACTOR SHALL REWORK HYDRONIC PIPING AND CONDENSATE PIPING AS REQUIRED TO RECONNECT UNIT TO EXISTING HYDRONIC BRANCH PIPING AND EXISTING CONDENSATE DRAIN PIPING. FIELD COORDINATE EXACT LOCATION WITH EQUIPMENT AND LIGHTS. COORDINATE LOCATION WITH ALL OTHER TRADES.
- ② EXISTING FAN COIL UNIT ELOCATED TO NOT BE IN CONFLICT WITH NEW FOODS LAB HOOD. CONTRACTOR SHALL REWORK HYDRONIC PIPING AS REQUIRED TO RECONNECT UNIT TO EXISTING HYDRONIC BRANCH PIPING. UNIT TO MOVE APPROXIMATELY 96" IN DIRECTION INDICATED. CONTRACTOR SHALL FIELD VERIFY EXACT DIMENSIONS AND COORDINATE FINAL LOCATION WITH ALL OTHER TRADES.
- (3) TURN DUCTWORK UP TO MAKE-UP AIR UNIT ON ROOF ABOVE. (4) NEW KITCHEN HOOD EXHAUST FANS MOUNTED ON ROOF ABOVE.
- (5) INSTALL NEW DRYER DUCT AND MANUFACTURER'S WALLCAP IN EXTERIOR WALL BELOW WINDOWS.
- 6 EXISTING FAN COIL TO REMAIN.
- 7 NEW FAN COIL. CONTRACTOR TO INSTALL IN NEW CLASSROOM AS INDICATED AND CONNECT NEW HOT AND CHILLED WATER BRANCH PIPING BACK TO PIPING MAINS. PROVIDE AND INSTALL NEW MODULATING HOT AND CHILLED WATER CONTROL VALVES AND CONNECT TO EXISTING CONTROL SYSTEM. SEE FAN COIL EQUIPMENT
- (8) REMOVE EXISTING FAN COIL AND REPLACE WITH NEW FAN COIL AND NEW CHILLED AND HOT WATER VALVES AS INDICATED IN THE FAN COIL EQUIPMENT SCHEDULE. COORDINATE LOCATION WITH LIGHTS. REWORK TRIM PIPING TO CONNECT BACK TO EXISTING CHILLED AND HOT WATER PIPING.
- PROVIDE AND INSTALL NEW TEMP—SENSOR AND HUMIDISTAT (CAN BE A COMBINATION UNIT) MOUNTED ON WALL NEAR CLASSROOM DOOR. CONNECT FC-304A AND FC-304B TO NEW SENSOR. TIE BACK TO EXISTING JOHNSON CONTROL SYSTEM.
- ALL EXISTING AND NEW HVAC EQUIPMENT SHALL BE TIED BACK TO
 THE EXISTING CONTROLS SYSTEM. PROVIDE ANY EXPANSION CARDS, PROGRAMMING, CONTROLLER RELOCATION, UPGRADES, ETC. NECESSARY TO HAVE A COMPLETE AND OPERATIONAL SYSTEM AT PROJECT COMPLETION. CONTROLS CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFYING EXISTING CONDITIONS, CONTROLLERS AND COORDINATING NEW EQUIPMENT WITH MC TO MAKE SURE IT WILL SMOOTHLY INTEGRATE INTO THE EXISTING SYSTEM.

FOOD LAB MECHANICAL PLAN SCALE: 1/4" = 1'-0"

MECHANICAL LEGEND G.C. GEN. CONTR.

E.C. ELEC. CONTR. P.C. PLUMB. CONTR. ABOVE FINISH FLOOR ABOVE FINISH GRADE

WRAPPED RIGID DUCT INSULATED FLEXIBLE DUCT SUPPLY DIFFUSER

CEILING EXHAUST GRILLE OR FAN THERMOSTAT & UNIT SERVED.

RETURN AIR GRILLE

HUMIDISTAT & UNIT SERVED. DIFFUSER TYPE-CFM

MANUAL DAMPER DUCT MOUNTED SMOKE DETECTOR CEILING MOUNTED

SMOKE DETECTOR FIRE ALARM HORN/STROBE (SEE GENERAL NOTES)


CONN. TO EXIST. GAS PIPING

SPRING LOADED FIRE DAMPER


CAHU-1 CO2 SENSOR (800 PPM)

TWIST TIMER SWITCH 120V MOTORIZED DAMPER

OAHU-1 CO SENSOR & UNIT SERVED. CNAHU-1 CO & NO SENSOR & UNIT SERVED.








ovation Chool Room Re High

Project No. 22111 26 AUGUST, 2024



CONNECTIONS.

INSTALLATION OF GAS PIPE IF ANY ONE OF THE

ABOVE CALCULATIONS DIFFER FROM THE ACTUAL

INSTALLATION REQUIREMENTS. ENGINEER SHALL HAVE OPPORTUNITY TO REVIEW ACTUAL INSTALLATION

CONDITIONS AND RE-SIZE GAS SERVICE IF REQUIRED

KEY PLAN ENGINEERING E-Mail Address: generalmail@engrsource.com Voice (252) 439-0338 * Fax (252) 439-0462 * Firm #C-1973

Project No. 22111

26 AUGUST, 2024

SPRING LOADED FIRE DAMPER

CO2 SENSOR (800 PPM) & UNIT SERVED.

120V MOTORIZED DAMPER

CNAHU-1 CO & NO SENSOR & UNIT SERVED.

TWIST TIMER SWITCH

OAHU-1 CO SENSOR & UNIT SERVED.